



PID Control Silicon Carbide Furnace Vacuum Heat Treatment 150 Watt Stable

Our Product Introduction

Basic Information

- Place of Origin: CHINA
- Brand Name: OEM
- Certification: CE Certification
- Model Number: OEM
- Minimum Order Quantity: Negotiable
- Price: Negotiable
- Packaging Details: Carton, pallet, wooden case or according to customer's package requirements
- Delivery Time: 30 working days
- Payment Terms: 30% deposit + 70% T/T before shipping
- Supply Ability: 20 sets per month



Product Specification

- Name: Vacuum Heat Treatment Furnace
- Feature: Easy Operation
- Dimension(L*W*H): Custom
- Cooling Method: Internal Circulation Cooling
- Max Operating Temp: 2450 ° C
- Application: Silicon Carbide, Ceramics
- Highlight: **high temperature vacuum furnace , vacuum brazing furnace**

for more products please visit us on newarrivals2025.com

Product Description

PID Control Silicon Carbide Furnace , Vacuum Heat Treatment Furnace 150w

Silicon Carbide Furnace Application:

Vacuum Heat Treatment Furnace Mainly used for recrystallization of silicon carbide

Silicon Carbide Furnace Main technical performance and indicators

Maximum operating temperature: 2450 ° C

Common temperature: 2400 ° C

Heating method: induction heating

Working gas in the furnace: nitrogen argon

Temperature uniformity: $\leq \pm 10^{\circ}\text{C}$

According to the needs of the sintering process time, multiple electric furnaces can be arranged in a single power supply, and the heating and cooling of the individual furnaces can be respectively performed to achieve continuous operation.

Temperature measurement: WRe5/26 thermocouple (0-1700 °C) + US RATEK dual colorimetric infrared thermometer (1000-3200 ° C); US RATEK monochrome infrared thermometer (300-1100 ° C) + US RATEK double ratio Color infrared thermometer (1000-3200 ° C)

Temperature control: PID intelligent program control and manual control

Superior process performance, making product quality a new step

The device adopts multi-channel data acquisition and displays and operates on the man-machine interface. The operating parameters are clear at a glance, the operation is simple, and the labor intensity is low;

The device has data recording and dumping functions, and the data can be viewed through the historical curve and can be transferred to the mobile storage medium;

Energy-saving, special coil and insulation structure, stable power output and high electrical efficiency.

Volume (L)	192	350	484	1920
Rated temperature (°C)	2400	2400	2400	2400
Limit temperature (°C)	2450	2450	2450	2450
Effective heating zone (mm)	400X400X1200	500X500X1400	550X550X1600	800X800X3000
Power (KW)	150	250	350	550
Frequency (HZ)	1500	1000	1000	1000
Temperature control method	Japanese island electric thermostat			
Vacuum system	Spool valve vacuum pump + Roots vacuum pump			
Sintering atmosphere	N2, Ar2, etc.			
Rated power supply voltage (V)	380			
Rated heating voltage (V)	According to the design, configure the transformer			
Vacuum limit (pa)	40 (vacuum cold state)			



Jinan Yinghua Outdoor Equipment Co., Ltd.



+8618812345678



Puooedr@maoyt.com



newarrivals2025.com

Room 402.Dongbao Building, No.19 Dongbao Road, Chaoyang, Beijing 201613, China