



## Sufficient Output Gas Fired Steam Boiler , Low Pressure Steam Boiler Stable

### Our Product Introduction

#### Basic Information

- Place of Origin: CHINA
- Brand Name: OEM
- Certification: CE Certification
- Model Number: OEM
- Minimum Order Quantity: Negotiable
- Price: Negotiable
- Packaging Details: Carton, pallet, wooden case or according to customer's package requirements
- Delivery Time: 30 working days
- Payment Terms: 30% deposit + 70% T/T before shipping
- Supply Ability: 20 sets per month



#### Product Specification

- Place Of Origin: China
- Output: Steam
- Rated Evaporation: 0.5-3t/h
- Rated Working Pressure: 0.7-1Mpa
- Saturated Steam Temperature: 170-184
- Fuel: Natural Gas
- Highlight: **natural gas steam boiler,  
gas powered steam boiler**

## Product Description

### Low Pressure Gas Fired steam Boiler For Sale

#### Product introduction

The horizontal structure boiler ,with adequate heating area, full heat transfer ,stable operating under load revise ,high combustion efficiency.

Boiler furnace located at low position ,ensure the safety range of the water level.Big steam evaporation surface, high quality steam .

Pre purge function, improve the working conditions of the burner and prolong the service life .

The unique design of the combustion chamber, increasing the radiation heating furnace area, shrinking the size of boiler, reducing NOx emissions.

#### Parameter

Rated evaporation		t/h	0.5	1	1.5	2	3
Rated working pressure		MPa	0.7	1	1	1	1
Saturated steam temperature			170	184	184	184	184
Fuel consumption	Light diesel oil	kg/h	35	70	105	140	210
	Natural gas	Nm³/h	40	80	120	160	240
	LPG	Nm³/h	15	30	45	60	90
	City gas	Nm³/h	85	170	250	340	510
a Main steam valve diameter		DN	40	65	65	80	80
b Safety valve diameter		DN	40	50	50	40×2	40×2
c Inlet diameter		DN	25	25	40	40	40
d Blowoff Valve diameter		DN	40	40	40	50	50
e Chimney diameter		DN	250	300	350	400	450
Overall size	L	mm	3800	4500	4700	4800	5500
	L1	mm	3100	3200	3600	3800	4500
	W	mm	1900	2300	2800	2900	2900
	W1	mm	1000	1880	1900	2150	2350
	H	mm	2100	2680	2950	3250	3880
	H1	mm	1800	1980	2070	2250	2450
Weight		T	3.3	4.6	5.5	6.3	10.6

#### Characteristics

- 1 . Burning clean, discharge without pollution
- 2 . Convenient operation and sufficient output
- 3 . Applicable fuel: natural gas,light diesel gas
- 4 . Scope of application: chemical, plastic, rubber, construction, forestry, pharmaceutical



Jinan Yinghua Outdoor Equipment Co., Ltd.

+8618812345678

Puooedr@maoyt.com

[newarrivals2025.com](http://newarrivals2025.com)

Room 402.Dongbao Building,No.19 Dongbao Road,Chaoyang,Beijing 201613,China