



## High Safety Gas Fired Steam Boiler , Energy Efficient Steam Boilers Multi Chain Protection

Our Product Introduction

### Basic Information

- Place of Origin: CHINA
- Brand Name: OEM
- Certification: CE Certification
- Model Number: OEM
- Minimum Order Quantity: Negotiable
- Price: Negotiable
- Packaging Details: Carton, pallet, wooden case or according to customer's package requirements
- Delivery Time: 30 working days
- Payment Terms: 30% deposit + 70% T/T before shipping
- Supply Ability: 20 sets per month



### Product Specification

- Place Of Origin: China (Mainland)
- Type: Horizontal
- Rated Evaporation: 0.5-20T/h
- Rated Working Pressure: 0.7/1.0/1.25
- Saturated Steam Temperature: 170/184/193
- Fuel Consumption: Gas
- Highlight: natural gas steam boiler, lpg fired steam boiler

for more products please visit us on [newarrivals2025.com](http://newarrivals2025.com)

## Product Description

### New Energy - Saving Gas Fried Steam Boiler For Industry

#### Product introduction

The most mature design: three-way full wet back structure.

Furnace: Wave furnace.

Multi chain protection: Water level, steam pressure, gas pressure protection.

Unique heating chamber: unique design of large combustion chamber, it increased radiant heating furnace area, reducing boiler size and reducing NOx emissions.

Thermal efficiency: increase with threaded pipe and high effective insulation material Heat transfer and improve the thermal efficiency of the boiler.

Safety: All boilers undergo rigorous inspection and testing before delivery, including pressure testing and X-ray inspection and commissioning.

#### Parameter

Rated evaporation		t/h	0.5	1	1.5	2	3	4	6	8	10	12	15	20
Rated working pressure		MPa	0.7	1	1	1	1	1.25	1.25	1.25	1.25	1.25	1.25	1.25
Saturated steam temperature			170	184	184	184	184	193	193	193	193	193	193	193
Fuel consumption	Light diesel oil	kg/h	35	70	105	140	210	260	390	520	650	780	975	1300
	Natural gas	Nm <sup>3</sup> /h	40	80	120	160	240	280	420	560	700	840	1050	1400
	LPG	Nm <sup>3</sup> /h	15	30	45	60	90	120	180	240	300	360	450	600
	City gas	Nm <sup>3</sup> /h	85	170	250	340	510	680	1020	1360	1700	2040	2550	3400
a Main steam valve diameter		DN	40	65	65	80	80	100	125	150	150	200	200	250
b Safety valve diameter		DN	40	50	50	40×2	40×2	50×2	65×2	80×2	80×2	80×2	80×2	80×2
c Inlet diamater		DN	25	25	40	40	40	50	50	65	65	65	65	80
d Blowoff Valve diameter		DN	40	40	40	50	50	50	50	50	50	65	65	65
e Chimney diameter		DN	250	300	350	400	450	500	650	800	900	1000	1000	1250
Overall size	L	mm	3800	4500	4700	4800	5500	6310	7200	7780	8330	8740	10730	11250
	L1	mm	3100	3200	3600	3800	4500	5230	5960	6320	7040	7450	8110	8360
	W	mm	1900	2300	2800	2900	2900	2950	3190	3440	3475	3475	3850	4395
	W1	mm	1000	1880	1900	2150	2350	2350	2650	2980	3040	2700	2950	3250
	H	mm	2100	2680	2950	3250	3880	3120	3610	3700	3800	4050	4210	4650
	H1	mm	1800	1980	2070	2250	2450	2530	2850	2920	3050	3280	3510	3820
Weight		T	3.3	4.6	5.5	6.3	10.6	13.8	18.5	20	23	30.1	36.5	49.5

#### Advantage

1. Three return design
2. Stable and safe operation
3. The steam evaporation surface is large and the quality is good
4. Good natural circulation system



**Jinan Yinghua Outdoor Equipment Co., Ltd.**



+8618812345678



Puooedr@maoyt.com



newarrivals2025.com

Room 402.Dongbao Building,No.19 Dongbao Road,Chaoyang,Beijing 201613,China