



Central Heating Gas Fired Steam Boiler , High Efficiency Gas Steam Boiler

Our Product Introduction

Basic Information

- Place of Origin: CHINA
- Brand Name: OEM
- Certification: CE Certification
- Model Number: OEM
- Minimum Order Quantity: Negotiable
- Price: Negotiable
- Packaging Details: Carton, pallet, wooden case or according to customer's package requirements
- Delivery Time: 30 working days
- Payment Terms: 30% deposit + 70% T/T before shipping
- Supply Ability: 20 sets per month



Product Specification

- Rated Evaporation: 0.15 -0.3T/h
- Rated Working Pressure: 7bar
- Saturated Steam Temperature: 170
- Structure: Fire Tube
- Style: Vertical
- Fuel: LPG/Natural Gas/Pipeline Gas
- Highlight: **natural gas steam boiler, lpg fired steam boiler**

for more products please visit us on newarrivals2025.com

Product Description

Factory Direct Sell Gas Fired Central Heating Steam Boiler

Product introduction

- 1 . Above products use vertical furnace no tubes , four return structure.
- 2 .This design effectively increasing smoke heat transfer to boiler water ,which improving thermal efficiency and good at energy saving .
- 3 . No pipe design could save boiler from scaled and destroyed.
- 4 . The heat evenly transfer to wall and fins, avoiding stress and extending service life.
- 5 . Compared with similar products ,LWS series has large combustion room and low out-let temperature.
- 6 . The thread smoke tubes are mainly convective heating surface.And the upper chamber could install the heat exchange ,which could help for maximum energy saving.

Parameter

Rated evaporation		t/h	0.05	0.1	0.15	0.2	0.3
Rated working pressure		MPa	0.7	0.7	0.7	0.7	0.7
Saturated steam temperature			170	170	170	170	170
Fuel consumption	Light diesel oil	kg/h	3.5	7	10.5	14	21
	Natural gas	Nm³/h	4	8	12	16	24
	LPG	Nm³/h	1.5	3	4.5	6	9
	City gas	Nm³/h	8.5	17	25.5	34	51
Dimension							
a Main steam valve diameter		DN	15	25	25	32	32
b Safety valve diameter		DN	20	25	25	25	25
c Inlet diameter		DN	15	20	20	20	20
d Blowoff Valve diameter		DN	20	20	25	25	25
e Chimney diameter		DN	100	120	150	150	200
Overall size	L	mm	870	1020	1150	1260	1270
	W	mm	930	1080	1260	1400	1570
	W1	mm	640	760	890	970	1040
	H	mm	1660	1750	1840	2160	2400
	H1	mm	1460	1480	1520	1840	2090
	φ Diameter	mm	630	750	880	960	1000
Weight		kg	330	470	610	780	850

Advantage

- Not contain water pipes or fire pipes
- The boiler will not be burnt due to scaling
- Provide high quality steam
- Large heat transfer coefficient and sufficient heat transfer
- Easy to install and maintain



Jinan Yinghua Outdoor Equipment Co., Ltd.



+8618812345678



Puooedr@maoyt.com



newarrivals2025.com

Room 402.Dongbao Building,No.19 Dongbao Road,Chaoyang,Beijing 201613,China