



Energy Saving Steam Gas Fired Boiler For Milk Soybean Cola line Sterilize

Our Product Introduction

Basic Information

- Place of Origin: CHINA
- Brand Name: OEM
- Certification: CE Certification
- Model Number: OEM
- Minimum Order Quantity: Negotiable
- Price: Negotiable
- Packaging Details: Carton, pallet, wooden case or according to customer's package requirements
- Delivery Time: 30 working days
- Payment Terms: 30% deposit + 70% T/T before shipping
- Supply Ability: 20 sets per month



Product Specification

- Rated Evaporation: 150-300kg/h
- Saturated Steam Temperature: 170
- Rated Working Pressure: Low Pressure
- Main Steam Valve Diameter: 25/32DN
- Output: Steam
- Weight: 610-850kg
- Highlight: **natural gas steam boiler,
gas powered steam boiler**

for more products please visit us on newarrivals2025.com

Product Description

Gas / LPG Fired Steam Boiler For Milk , Soybean , Cola line Steam Sterilize

Product introduction

1. Wilford boiler is used of vertical furnace without bile tubes, four return structure.
2. Effectively increasing heat transfer to the gas water heaters,improving the thermal efficiency and good energy saving effect.
3. No need for piping design, heat is evenly transferred to the wall and heat transfer fins to avoid pressure and extend service life.
4. The combustion room is large and the furnace biliary export low-temperature, the main thread pipe is convection heating surface, the upper chamber can install the heat exchange recovery to maximize saving energy.

Parameter

Rated evaporation		t/h	0.05	0.1	0.15	0.2	0.3
Rated working pressure		MPa	0.7	0.7	0.7	0.7	0.7
Staturated steam temperature			170	170	170	170	170
Fuel consumption	Light diesel oil	kg/h	3.5	7	10.5	14	21
	Natural gas	Nm³/h	4	8	12	16	24
	LPG	Nm³/h	1.5	3	4.5	6	9
	City gas	Nm³/h	8.5	17	25.5	34	51
Dimension							
a Main steam valve diameter		DN	15	25	25	32	32
b Safety valve diameter		DN	20	25	25	25	25
c Inlet diamater		DN	15	20	20	20	20
d Blowoff Valve diameter		DN	20	20	25	25	25
e Chimney diameter		DN	100	120	150	150	200
Overall size	L	mm	870	1020	1150	1260	1270
	W	mm	930	1080	1260	1400	1570
	W1	mm	640	760	890	970	1040
	H	mm	1660	1750	1840	2160	2400
	H1	mm	1460	1480	1520	1840	2090
	φ Diameter	mm	630	750	880	960	1000
Weight		kg	330	470	610	780	850

Feature

- 1 . Vertical structure design
- 2 . Built-in furnace
- 3 . Full heat exchange
- 4 . Good steam quality
- 5 . High combustion efficiency
- 6 . Operation is safe and stable

VIKING Jinan Yinghua Outdoor Equipment Co., Ltd.



+8618812345678



Puooedr@maoyt.com



newarrivals2025.com

Room 402.Dongbao Building,No.19 Dongbao Road,Chaoyang,Beijing 201613,China