



## P5.95 Floor Interactive LED Screen Hospital Wayfinding Screen Remote CMS Management Auto Brightness Adjustment 640x480mm

### Basic Information



### Product Specification

- Pixel Pitch: 5.95mm
- Panel Type: SMD3535
- Brightness: 1500 Cd/m2
- Refresh Rate: 7680Hz
- IP Rating: IP43
- Cabinet Size: 250x250mm
- Viewing Angle: 160° Horizontal/Vertical
- LED Type: SMD3535
- Module Resolution: 64x64
- Power Consumption: 300W/m2
- Operating Temperature: -20°C To +60°C
- Lifespan: 100000 Hours
- Highlight: **P5.95 LED screen hospital, 4500 nits brightness floor interactive led screen, Remote CMS Management SMD2121 display**

## Product Description

### Product Description

P5.95 Floor Interactive LED Screen designed for Hospital Wayfinding Screen. Features Remote CMS Management, Auto Brightness Adjustment, and 4500 nits brightness. Perfect for professional display solutions with 7680Hz refresh rate and IP54 protection.

### Key Features

- Remote CMS Management for easy content management
- Auto Brightness Adjustment for reliable operation
- 4500 nits outdoor brightness for clear visibility
- 7680Hz refresh rate for smooth video
- IP54 rated for weatherproof durability
- 640x480mm cabinet size for flexible installation

### Technical Specifications

Pixel Pitch	P5.95
Panel Type	SMD2121
Brightness	4500 nits
Refresh Rate	7680Hz
Viewing Angle	140°
IP Rating	IP54
Cabinet Size	640x480mm
Certification	CE RoHS

### Applications

Hospital Wayfinding Screen, outdoor advertising, event rental, retail display, and more.

 **Jinan Yinghua Outdoor Equipment Co., Ltd.**

+8618812345678

[Puooedr@maoyt.com](mailto:Puooedr@maoyt.com)

[newarrivals2025.com](http://newarrivals2025.com)

Room 402.Dongbao Building, No.19 Dongbao Road, Chaoyang, Beijing 201613, China