



P2.5 Bus Shelter LED Screen Shopping Mall Display Tool Free Installation Rear Maintenance Design 320x320mm

Basic Information



Product Specification

- Pixel Pitch: 2.5mm
- Panel Type: SMD2121
- Brightness: 7000 Nits
- Refresh Rate: 7680Hz
- IP Rating: IP66
- Cabinet Size: 500x500mm
- Viewing Angle: 160° Horizontal/Vertical
- LED Type: SMD2121
- Module Resolution: 64x64
- Power Consumption: 400W/m²
- Operating Temperature: -20°C To +60°C
- Lifespan: 100000 Hours
- Highlight: **P2.5 LED screen shopping, 4500 nits brightness bus shelter led screen, Tool Free Installation COB display**

Product Description

Product Description

P2.5 Bus Shelter LED Screen designed for Shopping Mall Display. Features Tool Free Installation, Rear Maintenance Design, and 4500 nits brightness. Perfect for professional display solutions with 7680Hz refresh rate and IP65 protection.

Key Features

- Tool Free Installation for easy content management
- Rear Maintenance Design for reliable operation
- 4500 nits outdoor brightness for clear visibility
- 7680Hz refresh rate for smooth video
- IP65 rated for weatherproof durability
- 320x320mm cabinet size for flexible installation

Technical Specifications

Pixel Pitch	P2.5
Panel Type	COB
Brightness	4500 nits
Refresh Rate	7680Hz
Viewing Angle	140°
IP Rating	IP65
Cabinet Size	320x320mm
Certification	CE RoHS FCC

Applications

Shopping Mall Display, outdoor advertising, event rental, retail display, and more.



Jinan Yinghua Outdoor Equipment Co., Ltd.



+8618812345678



Puooedr@maoyt.com



newarrivals2025.com

Room 402.Dongbao Building, No.19 Dongbao Road, Chaoyang, Beijing 201613, China