



P1.667 Flexible LED Display Wedding Event Display Magnetic Module Design Soft LED Module 500x500mm

Basic Information



Product Specification

- Pixel Pitch: 1.667mm
- Panel Type: IMD
- Brightness: 800 Cd/m²
- Refresh Rate: 1920Hz
- IP Rating: IP40
- Cabinet Size: 1000x1000mm
- Viewing Angle: 160° Horizontal/Vertical
- LED Type: IMD
- Module Resolution: 64x64
- Power Consumption: 350W/m²
- Operating Temperature: -20°C To +60°C
- Lifespan: 100000 Hours
- Highlight: **P1.667 LED screen wedding, 7000 nits brightness flexible led display, Magnetic Module Design GOB display**

Product Description

Product Description

P1.667 Flexible LED Display designed for Wedding Event Display. Features Magnetic Module Design, Soft LED Module, and 7000 nits brightness. Perfect for professional display solutions with 9600Hz refresh rate and IP67 protection.

Key Features

- 2711 Magnetic Module Design for easy content management
- 2715 Soft LED Module for reliable operation
- 2717 7000 nits outdoor brightness for clear visibility
- 2719 9600Hz refresh rate for smooth video
- 2718 IP67 rated for weatherproof durability
- 2716 500x500mm cabinet size for flexible installation

Technical Specifications

Pixel Pitch	P1.667
Panel Type	GOB
Brightness	7000 nits
Refresh Rate	9600Hz
Viewing Angle	170° Horizontal/Vertical
IP Rating	IP67
Cabinet Size	500x500mm
Certification	CE RoHS FCC

Applications

Wedding Event Display, outdoor advertising, event rental, retail display, and more.

 **Jinan Yinghua Outdoor Equipment Co., Ltd.**

+8618812345678

Puooedr@maoyt.com

newarrivals2025.com

Room 402.Dongbao Building, No.19 Dongbao Road, Chaoyang, Beijing 201613, China