



## P3 Window LED Display Museum Exhibition Panel Tool Free Installation 4G Remote Management 640x480mm

### Basic Information



### Product Specification

- Pixel Pitch: 3mm
- Panel Type: SMD2121
- Brightness: 800 Cd/m2
- Refresh Rate: 7680Hz
- IP Rating: IP43
- Cabinet Size: 960x960mm
- Viewing Angle: 160° Horizontal/Vertical
- LED Type: SMD2121
- Module Resolution: 64x64
- Power Consumption: 350W/m2
- Operating Temperature: -20°C To +60°C
- Lifespan: 100000 Hours
- Highlight: **P3 LED screen museum, 6000 nits brightness window led display, Tool Free Installation SMD3535 display**

Our Product Introduction

for more products please visit us on [newarrivals2025.com](http://newarrivals2025.com)

## Product Description

### Product Description

P3 Window LED Display designed for Museum Exhibition Panel. Features Tool Free Installation, 4G Remote Management, and 6000 nits brightness. Perfect for professional display solutions with 9600Hz refresh rate and IP66 protection.

### Key Features

- Tool Free Installation for easy content management
- 4G Remote Management for reliable operation
- 6000 nits outdoor brightness for clear visibility
- 9600Hz refresh rate for smooth video
- IP66 rated for weatherproof durability
- 640x480mm cabinet size for flexible installation

### Technical Specifications

Pixel Pitch	P3
Panel Type	SMD3535
Brightness	6000 nits
Refresh Rate	9600Hz
Viewing Angle	178° Wide
IP Rating	IP66
Cabinet Size	640x480mm
Certification	CE RoHS

### Applications

Museum Exhibition Panel, outdoor advertising, event rental, retail display, and more.

 **Jinan Yinghua Outdoor Equipment Co., Ltd.**

+8618812345678

[Puooedr@maoyt.com](mailto:Puooedr@maoyt.com)

[newarrivals2025.com](http://newarrivals2025.com)

Room 402.Dongbao Building, No.19 Dongbao Road, Chaoyang, Beijing 201613, China