



P1.25 Bus Shelter LED Screen Theme Park Attraction Display Timer Schedule Control Bluetooth Wireless 320x320mm

Basic Information



Product Specification

- Pixel Pitch: 1.25mm
- Panel Type: COB
- Brightness: 6500 Nits
- Refresh Rate: 3840Hz
- IP Rating: IP66
- Cabinet Size: 960x960mm
- Viewing Angle: 160° Horizontal/Vertical
- LED Type: COB
- Module Resolution: 64x64
- Power Consumption: 450W/m²
- Operating Temperature: -20°C To +60°C
- Lifespan: 100000 Hours
- Highlight: **P1.25 LED screen theme, 6500 nits brightness bus shelter led screen, Timer Schedule Control COB display**

Product Description

Product Description

P1.25 Bus Shelter LED Screen designed for Theme Park Attraction Display. Features Timer Schedule Control, Bluetooth Wireless, and 6500 nits brightness. Perfect for professional display solutions with 3840Hz refresh rate and IP67 protection.

Key Features

- Timer Schedule Control for easy content management
- Bluetooth Wireless for reliable operation
- 6500 nits outdoor brightness for clear visibility
- 3840Hz refresh rate for smooth video
- IP67 rated for weatherproof durability
- 320x320mm cabinet size for flexible installation

Technical Specifications

Pixel Pitch	P1.25
Panel Type	COB
Brightness	6500 nits
Refresh Rate	3840Hz
Viewing Angle	160°
IP Rating	IP67
Cabinet Size	320x320mm
Certification	UL FCC

Applications

Theme Park Attraction Display, outdoor advertising, event rental, retail display, and more.

 **Jinan Yinghua Outdoor Equipment Co., Ltd.**

+8618812345678

Puooedr@maoyt.com

newarrivals2025.com

Room 402.Dongbao Building, No.19 Dongbao Road, Chaoyang, Beijing 201613, China