



P4.81 Bus Shelter LED Screen Wedding Event Display SOS Emergency Display Cloud Content Sync 640x480mm

Basic Information



Product Specification

- Pixel Pitch: 4.81mm
- Panel Type: SMD2727
- Brightness: 7000 Nits
- Refresh Rate: 7680Hz
- IP Rating: IP66
- Cabinet Size: 500x500mm
- Viewing Angle: 160° Horizontal/Vertical
- LED Type: SMD2727
- Module Resolution: 64x64
- Power Consumption: 450W/m²
- Operating Temperature: -20°C To +60°C
- Lifespan: 100000 Hours
- Highlight: **P4.81 LED screen wedding, 5500 nits brightness bus shelter led screen, SOS Emergency Display SMD2727 display**

Product Description

Product Description

P4.81 Bus Shelter LED Screen designed for Wedding Event Display. Features SOS Emergency Display, Cloud Content Sync, and 5500 nits brightness. Perfect for professional display solutions with 3840Hz refresh rate and IP67 protection.

Key Features

- 2715 SOS Emergency Display for easy content management
- 2710 Cloud Content Sync for reliable operation
- 2715 5500 nits outdoor brightness for clear visibility
- 2713 3840Hz refresh rate for smooth video
- 2711 IP67 rated for weatherproof durability
- 2716 640x480mm cabinet size for flexible installation

Technical Specifications

Pixel Pitch	P4.81
Panel Type	SMD2727
Brightness	5500 nits
Refresh Rate	3840Hz
Viewing Angle	170° Horizontal/Vertical
IP Rating	IP67
Cabinet Size	640x480mm
Certification	CE RoHS

Applications

Wedding Event Display, outdoor advertising, event rental, retail display, and more.

 **Jinan Yinghua Outdoor Equipment Co., Ltd.**

+8618812345678

Puooedr@maoyt.com

newarrivals2025.com

Room 402.Dongbao Building, No.19 Dongbao Road, Chaoyang, Beijing 201613, China